


Photometric data files (LDT/IES) for various beam angles are available upon request.

OVERALL DIMENSIONS



Model Name Dimensions (L×X) mm

JLT-WP40060 : L 600 × X (260 - 420)

JLT-WP40120 : L 1200 × X (700 - 980)

JLT-WP40150 : L 1500 × X (900 - 1300)

SKU Brief Specs

014006006001 : 20W, 0.6m, finish product, 2600lm

024006006002 : 20W, 0.6m, complete SKD, 2600lm

014012012005 : 40W, 1.2m, finish product, 5200lm

024012012006 : 40W, 1.2m, complete SKD, 5200lm

014015015009 : 60W, 1.5m, finish product, 7800lm

024015015010 : 60W, 1.5m, complete SKD, 7800lm

PRODUCT OVERVIEW

A PC/PC high-performance, weather-resistant LED luminaire engineered specifically for demanding industrial environments. Featuring a robust, impact-proof polycarbonate housing and Diffuser, this fixture offers superior IP65/IP66 protection against dust/water. It supports versatile surface-mounted or suspended installation, combining rugged durability with exceptional energy efficiency.

KEY FEATURES

- Polycarbonate (PC) housing body
- Polycarbonate (PC) diffuser
- Stainless Steel clips 304
- High-efficiency LED light source
- Applicable For Emergency Solution
- Flexible Surface or Pendant Mounting
- Toolless Access
- IP65/IP66 weatherproof construction
- Long lifetime with low maintenance
- Suitable for Industrial lighting

APPLICATIONS

- Warehouses
- Parking Garages
- Loading Docks
- Manufacturing Facilities
- Corridors & Underpasses
- Industrial Lighting

TECHNICAL SPECIFICATIONS

Input Voltage : 220-240VAC, 50/60Hz

Power : (20 / 40 / 60) W

Luminous Flux : (2600 / 5200 / 7800) lm

Efficacy (lm/W) : 130 lm/W

Light Source : LED 2835, PCBA

CCT : 3000K / 4000K / 5700K

CRI : ≥80

IP Rating : IP65/IP66

IK Rating : IK08

Mounting : Surface or Pendant

Body Color : Grey / Opal Diffuser

Lifetime : 50,000 Hours

Warranty : 5 Years